

**Dear customer.**

**We are pleased that you have decided to purchase a new bicycle from KS-CYCLING.**

However, before you are able to pedal away you must assemble your bicycle with care. This is important for both its reliability and its durability.

This manual provides a large number of assembly and individual descriptions for the various bicycle components and assembly groups. It also provides an overview of the assembly procedure depending on the type of bicycle.

Some components have a selection of varying designs; in general the exact type can be taken from the offer belonging to your bicycle.

If you are still uncertain about something please contact our technician per email under: [technik@schalow-kroh.de](mailto:technik@schalow-kroh.de)

If you are uncertain about your technical abilities or whether you have the necessary tools at your disposal, we would recommend that you take the bicycle to a specialist for final assembly, for example bicycle repairs shop in your area.

Please note that your bicycle has to be “run in”. This means that some settings carried out on the unused bicycle during assembly may have to be repeated subsequent to the first 100 – 200 kilometres of use.

Some components such as wheels and pedal bearings first settle into position when under load. Final adjustments can be carried out once such components have settled properly.

Until then it is recommended that one rides the bicycle carefully and observes whether a component has settled into position or not.

Please take note of the general bicycle handling instructions on the next few pages.

We wish you pleasure with your new bicycle.

Your KS-CYCLING team.